

Hardener Kapci 651

Filler Hardener Kapci 621

1-Characteristic properties:

Hardener Kapci 651

Is a versatile aliphatic isocyanate hardener to be used in different products. When added to two-component paints "Kapcicryl" it gives a final film with very high gloss, excellent weathering resistance and outstanding chemical resistance.

Filler Hardener Kapci 621

Is specially designed for use with two-component filler Kapci 620 to give very fast drying properties and good sandability. The end product is hard and has very good adhesion on metal surfaces.

2-Usage

Hardener Kapci 651 is to be used with
Kapcicryl "Kapci 660".

Kapci clear coat "C888".

Filler Hardener Kapci 621 is to be used with

Two-component filler Kapci 620.

3-Mixing ratio :

Refer to the mixing ratios specified in the technical data sheets for each product separately.

4-Packaging:

Kapci 651: 1 l, 1/2 l and 1/4 l

Kapci 621: 1/4 l

5-Shelf life:

12 months at 20°C

6-Material safety data

When using these products it is required to comply with the national regulations for health and safety.

7-Flash points and transport classification

Product	<u>Flash point</u>	ADR
Kapci hardener 651	21-55°C	3-31C
Kapci hardener 621	21-55°C	3-31C

The data on the label of the products must be considered.

Storage and transportation should comply with the local laws

The information given in this data sheet is based upon our best knowledge and experience with the application conditions set to Kapci standards. The customers are requested to verify the results by their own selves to make sure that the product is suitable for their applications and application conditions.

This document is computer generated therefore it is not signed.

Issued on 30/10/2000

Page 1 of 1

Printed 28/04/2001

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.